

SPECTRUM WELDING SUPPLIES

HIRE • SALES • REPAIR • REFURBISH





BODE SAR 300

15 TONNE CAPACITY 5 415V 450mm 4600mm







T 01246 205 267

E info@spectrumweldingsupplies.co.uk

W spectrumweldingsupplies.co.uk

BODE SAR 300

SINGLE WHEEL WIDTH

Model	SAR 300 15 tonne (single wheel)	
Supply	415V Please confirm 3-phase 32amp 4 or 5 pin plug before order	
Controls	Handheld pendant controller 10mtr cable (forward / reverse / stop / variable speed)	
Rotation Speed Range	Variable speed from 130mm p/min to 1300mm per minute	
Drive 'Turning' Capacity	15 Tonnes	
Set (x1 Drive & x1 Idler Unit) Load Capacity	15 Tonnes	
Idler Rotator Load Capacity	7.5 Tonnes	
Drive Rotator Load Capacity	7.5 Tonnes	
Minimum Overall Diameter SWL	450mm	
Maximum Overall Diameter SWL	4600mm	
Minimum height rotators will raise cylinder off the ground (minimum wheel centres)	400mm	
Maximum height rotators will raise cylinder off the ground (maximum wheel centres)	600mm	
Wheel Overall Diameter	457mm	
Wheel Tyre Width	150mm x4 points per unit (8 off 150mm tyres points of contact per set)	
Wheel Edge Clearance	100mm (from edge of tyre to steel housing / drive guard – closest point)	
Wheel Material	Rubber	

Drive Unit Length	2660mm
Drive Unit Width	800mm
Drive Height	905mm
Drive Unit Weight	900kg

Idler Unit Length	2110mm
Idler Unit Width	572mm
Idler Height	905mm
Idler Unit Weight	500kg



Symbols



Load capacity



Supply voltage



Minimum overall diameter (mm)



Maximum overall diameter (mm)

