



SPECTRUM

WELDING SUPPLIES

HIRE • SALES • REPAIR • REFURBISH



BODE SAR 400

 20 TONNE CAPACITY  415V  450mm  4600mm

T 01246 205 267 E info@spectrumweldingsupplies.co.uk W spectrumweldingsupplies.co.uk







BODE SAR 400

TWIN
WHEEL WIDTH

Model	SAR 400 20 tonne (twin-wheel)
Supply	415V <i>Please confirm 3-phase 32amp 4 or 5 pin plug before order</i>
Controls	Handheld pendant controller 10mtr cable (forward / reverse / stop / variable speed)
Rotation Speed Range	Variable speed from 130mm p/min to 1300mm per minute
Drive 'Turning' Capacity	20 Tonnes
Set (x1 Drive & x1 Idler Unit) Load Capacity	20 Tonnes
Idler Rotator Load Capacity	10 Tonnes
Drive Rotator Load Capacity	10 Tonnes
Minimum Overall Diameter SWL	450mm
Maximum Overall Diameter SWL	4600mm
Minimum height rotators will raise cylinder off the ground (minimum wheel centres)	400mm
Maximum height rotators will raise cylinder off the ground (maximum wheel centres)	600mm
Wheel Overall Diameter	381mm
Wheel Tyre Width	76mm x 2 wheels (152mm) x 4 points per unit (16 x 76mm tyres points per set)
Wheel Edge Clearance	100mm (from edge of tyre to steel housing / drive guard - closest point)
Wheel Material	Rubber

Drive Unit Length	2884mm	Idler Unit Length	2010mm
Drive Unit Width	830mm	Idler Unit Width	600mm
Drive Height	871mm	Idler Height	871mm
Drive Unit Weight	1300kg	Idler Unit Weight	700kg

Symbols

-  Load capacity
-  Supply voltage
-  Minimum overall diameter (mm)
-  Maximum overall diameter (mm)





Spectrum Welding Supplies Ltd, Spectrum House,
McGregor's Way, Chesterfield, Derbyshire, S40 2WB

Registered Office: Spectrum House, McGregor's Way,
Chesterfield, Derbyshire, S40 2WB

Registered in England and Wales Company Registration No. 1732286

Vat Registration No. 401 5037 11