

HIRE • SALES • REPAIR • REFURBISH







MODEL CAPACITY: PEMA 30T

MAX LOAD CAPACITY ON 90° VERTICAL: 30,000kg @ 1000mm unsupported (balanced C of G) MAX LOAD CAPACITY ON 90° VERTICAL: 12,000kg @ 2000mm unsupported (balanced C of G) MAX ECCENTRICITY ON TITLED TABLE: 30,000kg @ 2000mm (OFFSET UNBALANCED JOB) MAX ECCENTRICITY ON TITLED TABLE: 6,000kg @ 2000mm (OFFSET UNBALANCED JOB)

TILTING TIME: 40 seconds 0 - 90 degrees DEGREE TABLE TILT: 110° hydraulic tilt MAX TILTING TORQUE: 300,000 NM

ROTATION SPEED ROTATION TORQUE: 55,000 NM

ROTATION SPEED: 0.01 (60 min revolution slowest) to 0.6 rpm (2 minute revolution fastest)

CONTROL: Cable pendant control (UP/DOWN/LEFT/RIGHT) ELECTRICAL SUPPLY: 3-phase 380V to 440V 50/60Hz INPUT CURRENT: 40amps (63amp plug needed)

LENGTH: 4100mm WIDTH: 2380mm

HEIGHT: 2510mm (LOW-LOADER STEP-BED TRAILER TRANSPORT REQUIRED TO DELIVER!)

TABLE WIDTH: 2400mm (8x bolting slots that are 27mm - 1" - wide)

HEIGHT FROM THE FLOOR TO CENTRE OF TILTED TABLE: 2180mm (2120mm centre of table to leg)
MAXIMUM JOB DIAMETER CAPACITY WITH VERTICAL TABLE: 4200mm (2120mm centre to leg)

LEG HEIGHT: 270mm

DISTANCE LEGS STICK OUT BEYOND VERTICAL TABLE: 750mm

MACHINE WEIGHT: 10.000KG



Spectrum Welding Supplies Ltd. Spectrum House, McGregor's Way, Chesterfield, Derbyshire, S40 2WB

T 01246 205267 E info@spectrumweldingsupplies.co.uk
W www.spectrumweldingsupplies.co.uk