

## SPECTRUM WELDING SUPPLIES

HIRE · SALES · REPAIR · SERVICES





## **ESAB A2 MULTITRAC PEK**

☆ 800amps

**T** 01246 205 267 **E** info@spectrumweldingsupplies.co.uk W spectrumweldingsupplies.co.uk

Available on our website





T 01246 205 267

**E** info@spectrumweldingsupplies.co.uk

W spectrumweldingsupplies.co.uk

## 800AMP ESAB LAF 1001 A2 PEK 4-WHEEL 25MTR SUBMERGED ARC WELDER TRACTOR

A2 Multitrac is a compact versatile tractor suitable for both butt and fillet welds with extremely fast change over time.

## **Features:**

- Choose single or twin wire
- The feed unit secures an even, stable wire feed speed
- Four-wheel drive ensures accurate travel speed
- Digital control panel allows exact pre-set and control of welding parameters
- A2 Multitrac is fully mobile and can easily be moved from one welding station to another
- Can be quickly set-up for different workpieces designed for use with ESAB LAF (DC), TAF (AC), and ARISTO® 1000 AC/DC welding power sources

A2 Multitrac PEK	Single SAW	Twin SAW
Wire diameters, in. (mm) Steel Stainless steel Corded wire Aluminium	1/16-5/32 (1.6-4.0) 1/16-5/32 (1.6-4.0) 1/16-5/32 (1.6-4.0)	2x0.45x3/32 (2x1.2-2.5) 2x0.45x3/32 (2x1.2-2.5) -
Max wire feed speed, ipm (m.min)	354 (9)	354 (9)
Wire reel weight, lbs. (kg)		2x33 (2x15)
Flux hopper capacity, gal. (L)	1.4 (6)	1.4 (6)
Permissible load 100%, A	800	800
Control voltage, V AC	42	42
Travel speed, ipm (m/min)	4-67 (0.1-1.7)	4-67 (0.1-1.7)
Linear slides stroke length, in. (mm)	3.5 (90)	3.5(90)
Rotary slide setting angle	360°	360°
Weight, excl wire and flux, lbs. (kg)	104 (47)	104 (47)







