Versotrac EWT 1000

Designed to conquer your jobsite





The SAW version of Versotrac

Industry

- Bridge Construction Industry
- Marine and Offshore Industry
- Metal Beam Fabrication
- Pressure Vessels
- Ship and Offshore Yards
- Ship/Barge Building
- Structural Steel Fabrication
- Tank and Vessel Fabrication
- Windtower

With more than 70 years of experience from welding tractors ESAB brings you the most flexible and versatile tractor on the market. Versotrac has been designed with the input from real life experience of welders all over the world.

- Modularised system where the tractor can be disassembled into smaller units in less than 5 minutes, carried separately and easily brought through round holes of Ø 500 mm (20 in.) or manholes of 580 x 400 mm (23 x 16 in.)
- Robust wire feed mechanism that can weld mild steel wire up to 5 mm up to 1000A @ 100%
- The automatic weld head detection and setup lets you change between SAW and GMAW in no time
- Intuitive user interface with real-time heat input keeps you in control of the weld
- Introducing an all-new ergonomic handling system for welding wire spools, making wire changes easy
- Tool-less interaction makes it easy to change weld point position and switch between butt and fillet welding
- Re-buildable between three- and four-wheel versions to suit your needs
- Connect to analogue controlled SAW power sources from other brands with the optional Welding power source interface
- 4WD version available when using long cables
- Wire straightener with memory function
- Order the chassis and add the required head
- Positioning and setting using vertical slide (220 mm) and horizontal slide (±47.5 mm)

Visit **esab.com** for more information.

Versotrac EWT 1000

| Specifications | | |
|--|-----------------------------------|--|
| Max Spool Weight | 2 x 30 kg (2 x 66 lbs) | |
| Flux Capacity | 6 I (1.6 gal) | |
| Travel Speed | 0.1 – 2.0 m/min (4 – 78.7 in/min) | |
| Operating Temperature | -10 to +40 °C (+14 to +104 °F) | |
| Weight Tractor (excl head and bobbin holder) | 45 kg (99 lbs) | |
| Weight Head (excl flux) | 17 kg (37.4 lbs) | |
| Weight Bobbin Holder (excl wire) | 6 kg (13.2 lbs) | |

| Specifications Versoarc Welding Heads | | | | | |
|--|--|--|---------------------------------|--|--|
| | EWH 1000 SAW single | EWH 1000 SAW twin | EWH 600 GMAW | | |
| Wire Diameter, Mild Steel | 1.6 – 5.0 mm (1/16 – 3/16 in.) | - | 0.8 – 2.5 mm (0.030 – 3/32 in.) | | |
| Wire Diameter, Stainless Steel | 1.6 – 4.0 mm (1/16 – 5/32 in.) | - | 0.8 – 1.6 mm (0.030 – 1/16 in.) | | |
| Wire Diameter, Cored Wire | 1.6 – 5.0 mm (1/16 – 3/16 in.) | - | 1.2 – 3.2 mm (0.045 – 1/8 in.) | | |
| Wire Diameter, Twin Wire, * Mild steel | 2 x 1.2 – 3.2 mm (2 x 0.045 – 1/8 in.) | 2 x 1.2 – 1.6 mm (2 x 0.045 – 1/16 in.) | - | | |
| Wire diameter, Twin Wire, * Stainless steel | 2 x 1.2 – 2.5 mm (2 x 0.045 – 3/32 in.) | 2 x 1.2 – 1.6 mm (2 x 0.045 – 1/16 in.) | - | | |
| Max Wire Feed Speed | 9.0 m/min (354.3 in/min) | 16.0 m/min (630 in/min) | 16.0 m/min (630 in/min) | | |
| Max Current | 1000 A @ 100% | 1000 A @ 100% | 600 A @ 100% | | |

^{*} Optional twin kit is needed





Versotrac EWT 1000

| Ord | Ordering Information Order the chassis, add the required head and 1-2 portable wire bobbin holders | | | |
|-----|--|------------|--|--|
| 1. | Versotrac EWT 1000 Tractor Chassis with 2 wheel drive w/o head | 0904200890 | | |
| 1. | Versotrac EWT 1000 Tractor Chassis with 4 wheel drive w/o head | 0904200891 | | |
| 2. | Versoarc EWH 1000 (SAW) Welding Head Single wire | 0904520880 | | |
| 2. | Versoarc EWH 1000 (SAW twin high speed) Welding Head * | 0904520884 | | |
| 2. | Versoarc EWH 600 (GMAW) Welding Head | 0904520885 | | |
| 3. | Portable Wire Bobbin Holder | 0908520880 | | |

^{*} Requires two Portable Wire Bobbin Holders 0908520880 when used in combination with Versotrac.

| Options & Accessories | |
|---|------------|
| Lamp kit (2x27W LED) | 0904273880 |
| Guide Wheel Bogie | 0413542880 |
| Idling Roller (2 per tractor) | 0446151880 |
| Guide Rail, 3 m (10 ft.) | 0154203880 |
| Grooved steel wheels for guide rail support, 1 wheel | 0443682880 |
| Grooved steel wheels for guide rail support, set of 4 | 0443682881 |
| 3-wheel Kit | 0904557880 |
| Steering Handle (for steering of 3-wheel version) | 0904537880 |
| Flat Fillet Kit | 0904586880 |
| Laser Lamp Kit | 0821440984 |
| Wire Reel Holder 30 kg (66 lbs), Plastic | 0153872880 |
| Welding Power Source Interface 115 VAC | 0446180880 |
| Welding Power Source Interface 230 VAC | 0446180881 |
| Twin Kit EWH 1000 (Conversion from single to twin wire set-up) * | 0446110880 |
| 4WD Kit, recommended for cables longer than 15 m (45 ft), for Serial numbers after 905-207-XXXX | 0910053880 |
| 4WD Kit, recommended for cables longer than 15 m (45 ft) incl. new wheels, for Serial numbers before 905-207-XXXX | 0910531880 |

For more information on Versoarc EWH, EAC 10 controller or wear parts please see separate fact sheet or manual.



ESAB / esab.com









^{*} Always order in combination with an additional Portable Wire Bobbin Holder 0908520880