

WARRIOR EDGE 500 CX

Powerful multi-process pulse welding power source



Warrior Edge 500 CX is an easy-to-use, high-performing and connected multi-process welding machine, featuring the WeldModes Pulse and SPEED.

- **PULSE** WeldMode – adaptive pulse MIG process optimized to compensate for operator variation with an easy, user-friendly setup designed to achieve excellent weld results
- **SPEED** WeldMode – provides a focused arc that allows the welder to control the weld puddle at higher travel speeds thus increasing the productivity, on steel, stainless steel, and aluminium.
- **WeldCloud** – integrated connectivity
- Optional cooling unit

RobustFeed Edge features

- **TrueFlow** – digital gas flow control system from ESAB, effectively manages shielding gas, both in starts and while welding thus improving quality and decreasing consumption
- **Hybrid HMI** – material selection and configurations on a TFT screen inside the unit with a clear and easy to use external display for everyday operation makes unit intuitive to operate
- **Operator Management** – quick to set-up system with RFID key card that allows locking down quick-jobs with limit setting that improves repeatability and adherence to welding procedure specifications
- **SpoolSafe** – unique in the market, IP54 protection against dust, dirt, and other debris that keeps your wire dry and clean, improves feedability and reduces risk of contaminations of the weld
- **PreciDrive** – wire drive system that maintains precision wire feeding performance to promote consistent weld quality
- **Red Dot design award 2021** – winning design provides well-designed ergonomics and intuitive user interface that reduces operator training needs



reddot design award
winner 2021

Warrior Edge 500 CX and
RobustFeed Edge CX

Industry

- Industrial and General Fabrication
- Structural Steel Fabrication
- Transportation
- Railcars
- Mobile Equipment
- Tank and Vessel Fabrication
- Pressure Vessels
- Energy
- Marine/Offshore

Visit **esab.com** for more information.

WARRIOR EDGE 500 CX

Specifications	
Mains Voltage	380 - 460 V ±10%, 3Φ, 50/60 Hz
Welding Output GMAW (MIG/MAG)	500 A / 39.0 V at 60% Duty Cycle 400 A / 34.0 V at 100% Duty Cycle
Welding Output SMAW (Stick)	500 A / 40.0 V at 60% Duty Cycle 400 A / 36.0 V at 100% Duty Cycle
Welding Output GTAW (TIG)	500 A / 30.0 V at 60% Duty Cycle 400 A / 26.0 V at 100% Duty Cycle
Setting Range GMAW (MIG/MAG)	8 A / 8.0 V - 500 A / 44 V
Setting Range SMAW (MMA)	8 A / 20.3 V - 500 A / 40 V
Setting Range GTAW (TIG)	4 A / 10.2 V - 500 A / 30 V
Standby Power	43 W
Open Circuit Voltage	54.8 V
Efficiency at Max Current (MMA)	89%
Power Factor at Max Current (MMA)	0.91
Efficiency at Max Current MIG/MAG	88%
Power Factor at Max Current MIG/MAG	0.93
Dimensions L x W x H	700 x 325 x 680 mm
Weight	85 kg
Operating Temperature	-20 to +55°C
Enclosure Class	IP23
Application Class	S
Insulation Class	H
Certification Mark (Standards)	CE
Cooling Unit, Optional Cool2	
Cooling Power	1.0 kW
Coolant Volume	4.5 l
Max Flow	1.8 l/min
Max Pressure	4.6 bar

Selection Guide Power Source										
Description	Part Number	Cooler	Hybrid HMI	SYN	PULSE	SPEED	THIN	CRAFT	ROOT	ROOT PIPE
Warrior Edge 500 CX I (CE)	0448500880	Optional	X	X	X					
Warrior Edge 500 CX II (CE)	0448500881	Optional	X	X	X	X				
Warrior Edge 500 DX (CE Water)	0446300886	Integrated 1.4 kW	X	X	X	X	X	X	X	X

Selection Guide Wire Feeder									
Description	Part Number	Spoolsafe IP54	Dual HMI	RFID Panel Lock	Trueflow Digital Gas Control	Heater	MMA OKC	Push/Pull Capable	
RobustFeed Edge BX (CE)	0446600880	X	X	X					
RobustFeed Edge CX (CE)	0446600881	X	X	X	X	X			
RobustFeed Edge DX (CE)	0446600882	X	X	X	X	X	X	X	

WARRIOR EDGE 500 CX

Ordering Information

Warrior Edge 500 CX I, 380-460 V, CE	0448500880
Warrior Edge 500 CX II (incl. SPEED), 380-460 V, CE	0448500881

Wire Feeder & Control Panel

RobustFeed Edge BX, Water-cooled, Euro	0446600880
RobustFeed Edge CX, Water-cooled, Digital Gas Control, Heater, Euro	0446600881
RobustFeed Edge DX, Water-cooled, Digital Gas Control, Heater, Rear OKC, Euro, Push-Pull Capable	0446600882

For complete list of wire feeder accessories and interconnection cables, see separate fact sheets or instruction manual.

Options & Accessories

Description	Part Number
Cool 2	0465427880
Coolant Liquid, 10 l	0465720002
4-wheel Trolley, Power Source	0349313450
Counterbalance Arm with Stabilizer Kit, for 3 in 1 Trolley	0448181880
Counterbalance Arm Extension Kit for use with 6m and 7.5m torches	0448116880
Wheel Kit, Power Source	0465416880
Feeder Mounting Kit, Power Source Assembly incl. cable holders	0447518880
RobustFeed Wheel Kit *	0446081880
Guide Pin Extension Kit *	0465508880
Torch Holder RobustFeed	0446958880
Torch Strain Relief RobustFeed	0446082880
Boom Adaptor (Lifting Device)	0446956880
Quick Connector Marathon Pac	F102440880
4-wheel Feeder Trolley for >300 mm Spools	0349313700
RFID Admin Card Kit, 5 Cards (2 incl with RobustFeed)	0447776880
RFID User Card Kit, 5 Cards (3 incl with RobustFeed)	0447776881
WiFi & BT dongle for connectivity	0349313733
Remote User Interface, RobustFeed EDGE	0448850880
Control Cable, 2m	0349314654
Control Cable, 5m	0349314652
Control Cable, 10m	0349314650
Remote connector kit (CX only) **	0464663122

* Guide Pin Extension Kit 0465508880 required when Wire Feeder Wheel Kit is used in combination with Trolley 0349313450.

** Remote connector kit is required to be installed when Remote User Interface is used in conjunction with CX I or CX II power supplies.

WARRIOR EDGE 500 CX

Torches

Description	3 m	4 m	5 m
Exeor MIG 4.0G ² , Gas-Cooled *	0700025752	0700025753	0700025754
Exeor MIG 4.0G ² CX, Gas-Cooled, Up/down **	0700025755	0700025756	0700025757
Exeor MIG 4.0G ² DX, Gas-Cooled, Graphic Display***	0700025758	0700025759	0700025760
Exeor MIG 4.0W ² , Water-Cooled *	0700026050	0700026051	0700026052
Exeor MIG 4.0W ² CX, Water-Cooled, Up/down **	0700025730	0700025731	0700025732
Exeor MIG 4.0W ² DX, Water-Cooled, Graphic display ***	0700025733	0700025734	0700025735

* Torch with enhanced cooling performance.

** Torch with enhanced cooling performance. Includes Torch LED light and CX remote for JOB selection / WFS / V, 2T/4T

*** Torch with enhanced cooling performance. Includes Torch LED light and DX graphical display remote for JOB selection / WFS / V / 2T/4T / Measure values, Arc Dynamics

For more information on Exeor torches, see separate fact sheet.


Push Pull Torches

Description	8 m	12 m
PP 350w, Inline push-pull, EURO	0700026191	0700026192

For more information on PP350W torches, see separate fact sheet.

Interconnection Cables, incl. strain relief

Length	70mm ²		95 mm ²	
	Gas-Cooled	Water-Cooled	Gas-Cooled	Water-Cooled
2.0 m	0446310880	0446310890	0446310980	0446310990
5.0 m	0446310881	0446310891	0446310981	0446310991
10.0 m	0446310882	0446310892	0446310982	0446310992
15.0 m	0446310883	0446310893	0446310983	0446310993
20.0 m	0446310884	0446310894	0446310984	0446310994
25.0 m	0446310885	0446310895	0446310985	0446310995
35.0 m	0446310886	0446310896	0446310986	0446310996



Remote User Interface



Exeor MIG 4.0G², 4.0G² CX and 4.0G² DX Torches



PP 350w Inline Push-pull



ESAB / esab.com

